

Technical Specifications

Power connection

Voltage	110	V
Type of current	1~ 50	Hz
Connected load	2.6	kW
Mains fuse (delayed action)	30	A
Extension cable 10 m	2.5	mm ²

Water connection

Supply temperature (max.)	60	°C
Supply rate (min.)	700	l/h
Supply hose – length	7.5	m
Supply hose – diameter (min.)	½	inches
Supply pressure (max.)	10	bar
Suction height from open tank at a water temperature of 20 °C	0.5	m

Performance data

Operating pressure	20-100	bar
Flow rate	150-580	l/h
Detergent intake	0-40	l/h
Recoil force of hand-held spray gun at operating pressure (max.)	30	N

Noise emission

Sound pressure level (EN 60704-1)	78	dB(A)
Guaranteed sound power level (2000/14/EC)	98	dB(A)

Unit vibration


Total vibration value (ISO 5349)	2.8	m/s ²
----------------------------------	-----	------------------

Dimensions

Length/Width/Height	500/310/350	mm
Weight without accessories	29	kg
Oil quantity	0.5	l
Oil type (order no. 6.288-050)	motor oil	15W40

Circuit diagram

- C1** Capacitor
K1 Contactor
M1 Motor
Q1 Overload protection switch
Q2 Switch



HD 600 *GB

1.284-107.0

