

Technical specifications

		1.520-128.0
Main Supply		
Voltage	V	240
Current type	Hz	1~ 50
Connected load	kW	2,2
Protection (slow, char. C)	A	16
Type of protection		IPX5
Extension cord 30 m	mm ²	2,5
Water connection		
Max. feed temperature	°C	60
Min. feed volume	l/h (l/min)	600 (10)
Suck height from open container (20 °C)	m	1
Max. feed pressure	MPa (bar)	1,2 (12)
Performance data		
Working pressure	MPa (bar)	11,5 (115)
Nozzle size (CX)		036
Max. operating over-pressure	MPa (bar)	13 (130)
Water flow rate	l/h (l/min)	500 (8,3)
Detergent suck in	l/h (l/min)	0...25 (0...0,42)
Max. recoil force of hand spray gun	N	21
Values determined as per EN 60355-2-79		
Hand-arm vibration value		
Hand spray gun	m/s ²	2,55
Spray lance	m/s ²	<2,5
Uncertainty K	m/s ²	1
Sound pressure level L _{pA}	dB(A)	73
Uncertainty K _{pA}	dB(A)	2
Sound power level L _{WA} + Uncertainty K _{WA}	dB(A)	88
Dimensions and weights		
Length	mm	360
Width	mm	375
Height	mm	925
Weight without accessories	kg	25